



MAJESTIC
SYNTHETIC BLEND TECHNOLOGY

Advanced Synthetic Blend Technology

**PROVEN FORMULA FOR
EXTENDED PERFORMANCE**



Unit 19-20, 3615
Laird Rd, Mississauga, ON

647-761-3033

sales@majesticlubricantscanada.ca



Majestic Synthetic Oil Company is a leading provider of heavy-duty motor oil, gear/differential oils, hydraulic oils, antifreeze, grease, and various other industrial/machinery lubricants. Our company's philosophy is based on the belief that only top-quality lubricants produced using the latest innovative technology should be utilized in the market today. Majestic proudly blends and packages its products in Houston, Texas, and is certified by the American Petroleum Institute (API). Our complete range of products and our attentiveness to customer service ensures complete customer satisfaction.

Quality and customer satisfaction are our top priority. All of our products meet or exceed the latest specifications set for by the SAE, API, ILSAC and various other industry and governmental regulatory agencies. Majestic Synthetic Oil Company:

- Ensures excellent performance, reliability, and longevity
- Maintains professional client relationships
- Provides first class lubricants products

Why Majestic?

Our Majestic product line encompasses a full range of high-quality lubricants with applications across various industries. We manufacture and package synthetic and conventional products that include heavy duty engine oil, hydraulic oil, gear oil, transmission fluid, antifreeze, and grease, among others. We offer the full line of Majestic products in various sizes, including totes, drums, gallons, and quarts. Majestic products can also be purchased in bulk.

Majestic is strategically located in Houston, an area that represents more than 70 percent of the US lubricant market and has a rich history of servicing the petrochemical industry nationwide. "Best-in-class" sales representatives, responsive distribution and customer service teams, and quality products make Majestic stand above its competitors. Through our dedicated employees and staff, we focus individually on each of our clients' needs, and our clients have come to rely on Majestic's entrepreneurial ingenuity to cost effectively solve equipment reliability issues through our product offerings.

Majestic Customers

Automotive/diesel engine workshops, wholesalers, distributors, retail shops, and gas stations use or sell various Majestic products. We have established relationships with all types of vendors and are knowledgeable of specific lubricant needs within each industry.





HEAVY DUTY

ENGINE OIL

Majestic blended engine oil is premium grade diesel engine oil that provides excellent protection for newer, high performance engines.

Advanced Synthetic Blend Technology



- Multi-viscosity, thermally stable and durable formulation
- Equipped for diesel engines with an exhaust after treatment system
- Fuel saving properties and oxidation stability
- High viscosity index
- High dispersancy & detergency levels





Majestic 15W-40, 15W-50, 20W-50, and 10W-30 Heavy Duty Motor Oils are high-performance multi-grade para-synthetic lubricants, designed for use in high speed, four-stroke diesel engines, carbureted, fuel injected, turbo-charged and supercharged gasoline engines. Majestic 15W-40, 15W-50, 20W-50, and 10W-30 Heavy Duty Motor Oils provide superior protection against wear, corrosion, oxidation and varnish. Our unique detergent additive prevents sludge or carbon deposits in extreme heat or pressure conditions. Majestic Heavy Duty Motor Oils are formulated with high viscosity-index Type II paraffinic and synthetic base stocks to provide superior anti-shear properties, enhances engine performance and extend oil life. Majestic Heavy Duty Motor Oils are designed to ease cold-starts and eliminate viscosity breakdown.

Attributes:

- High performance multi-grade para-synthetic lubricant
- Designed for use in high speed, four-stroke diesel engines
- Designed for use in carbureted, fuel injected, turbo-charged and supercharged gasoline engines
- Designed for superior protection against wear, corrosion, oxidation and varnish
- Unique detergent additive prevents sludge or carbon deposits in extreme heat or pressure conditions
- Formulated with high viscosity-index Type II paraffinic and synthetic base stocks
- Superior anti-shear properties
- Enhances engine performance
- Extends oil life
- Eases cold-starts
- Eliminates viscosity breakdown

Product Availability

SAE 15W-40

4/1 Gal	4/3.78 L	MAJ15W40G
3/2 Gal	3/7.57 L	MAJ15W402G
5 Gal	18.92 L	MAJ15W405G
55 Gal	208.17 L	MAJ15W4055G
275 Gal	1040.87 L	MAJ15W40TG

SAE 15W-50

3/2 Gal	3/7.57 L	MAJ15W502G
5 Gal	18.92 L	MAJ15W505G
55 Gal	208.17 L	MAJ15W5055G
275 Gal	1040.87 L	MAJ15W50TG

SAE 20W-50

3/2 Gal	3/7.57 L	MAJ20W502G
5 Gal	18.92 L	MAJ20W505G
55 Gal	208.17 L	MAJ20W5055G
275 Gal	1040.87 L	MAJ20W50TG

SAE 10W-30

4/1 Gal	4/3.78 L	MAJ10W30G
3/2 Gal	3/7.57 L	MAJ10W302G
5 Gal	18.92 L	MAJ10W305G
55 Gal	208.17 L	MAJ10W3055G
275 Gal	1040.87 L	MAJ10W30TG



Light Duty

Majestic SAE 0W-20, SAE 5W-20, SAE 5W-30, and SAE 10W-30 Full Synthetic Light-Duty Motor Oils are multi-viscosity engine oils formulated with synthetic base oils and premium additives. These oils are designed for use in carbureted, fuel injected, turbocharged, and supercharged gasoline engines which require ILSAC GF-5, API SN Plus performance. These oils are especially effective in minimizing wear and extending engine life.

Product Availability

0W-20	1 Quart	.95 L	MAJLDS0W20Q
	55 Gal	208.17 L	MAJLDS0W2055G
	275 Gal	1040.87 L	MAJLDS0W20TG
5W-20	1 Quart	.95 L	MAJLDS5W20Q
	55 Gal	208.17 L	MAJLDS5W2055G
	275 Gal	1040.87 L	MAJLDS5W20TG
5W-30	1 Quart	.95 L	MAJLDS5W30Q
	55 Gal	208.17 L	MAJLDS5W3055G
	275 Gal	1040.87 L	MAJLDS5W30TG
10W-30	1 Quart	.95 L	MAJLDS10W30Q
	55 Gal	208.17 L	MAJLDS10W3055G
	275 Gal	1040.87 L	MAJLDS10W30TG

- High performance multi-grade full synthetic lubricants
- Designed for use in carbureted, fuel injected, turbocharged and supercharged gasoline engines
- Formulated with Type II synthetic base stocks
- Enhances engine performance
- Extends engine life



Motor Oil



Majestic SAE 5W-20, SAE 5W-30, SAE 10W-30 and SAE 10W-40 Synthetic Blend Light-Duty Motor Oils are multi-viscosity engine oils formulated with a blend of conventional and synthetic base oils and premium additives. These oils are designed for use in carbureted, fuel injected, turbocharged, and supercharged gasoline engines which require ILSAC GF-5, API SN performance. These oils are especially effective in minimizing wear and extending engine life.

Product Availability

5W-20	1 Quart	.95 L	MAJLD5W20Q
	55 Gal	208.17 L	MAJLD5W2055G
	275 Gal	1040.87 L	MAJLD5W20TG
5W-30	1 Quart	.95 L	MAJLD5W30Q
	55 Gal	208.17 L	MAJLD5W3055G
	275 Gal	1040.87 L	MAJLD5W30TG
10W-30	1 Quart	.95 L	MAJLD10W30Q
	55 Gal	208.17 L	MAJLD10W3055G
	275 Gal	1040.87 L	MAJLD10W30TG
10W-40	1 Quart	.95 L	MAJLD10W40Q
	55 Gal	208.17 L	MAJLD10W4055G
	275 Gal	1040.87 L	MAJLD10W40TG

- High performance multi-grade synthetic blend lubricants
- Designed for use in carbureted, fuel injected, turbocharged and supercharged gasoline engines
- Formulated with a blend of conventional and synthetic base stocks
- Enhances engine performance
- Extends engine life





Hydraulic Oil



Majestic ISO 32AW, 46AW, and 68AW Hydraulic Oils are formulated with high viscosity-index paraffinic base stocks and premium performance additives to provide excellent oxidation stability, corrosion protection, shear stability, and pumpability. This product is designed for wide array of operating conditions and temperatures. Our comprehensive additive package includes anti-wear, anti-corrosion, anti-foaming agents as well as detergency. Majestic ISO 32AW, 46AW, and 68AW Hydraulic Oils resists oxidation, rust, corrosion, foaming, varnish, and wear. Majestic R&O Hydraulic Oil offers protection against rust oxidation and corrosion. This is an economical multipurpose oil, suitable for use in a wide variety of industrial applications.

ISO 32 AW, 46 AW, and 68 AW Attributes:

- Formulated with high viscosity-index paraffinic base stocks and premium performance additives
- Excellent oxidation stability, corrosion protection, shear stability, and pumpability
- Designed for wide array of operating conditions and temperatures
- Comprehensive additive package includes anti-wear, anti-corrosion, anti-foaming agents as well as detergency
- Acceptable for a wide-range of applications
- Deters oxidation, rust, corrosion, foaming, varnish, and wear

R&O Attributes:

- Protection against rust and oxidation
- Protection against corrosion
- Low foaming
- Wide variety of industrial applications
- Economical multi-purpose oil



HIGHLY RECOMMENDED FOR:

- Vacuum pumps
- Nonconductive hydraulic fluid
- Bearings and gears
- Applications where general non-detergent type oils are applicable
- Hydraulic components: (valves, motors, servos, pumps, etc.)



Product Availability

HYDRAULIC 32	5 Gal	18.92 L	MAJAW325G
	55 Gal	208.17 L	MAJAW3255G
	275 Gal	1040.87 L	MAJAW32TG
HYDRAULIC 46	5 Gal	18.92 L	MAJAW465G
	55 Gal	208.17 L	MAJAW4655G
	275 Gal	1040.87 L	MAJAW46TG
HYDRAULIC 68	5 Gal	18.92 L	MAJAW685G
	55 Gal	208.17 L	MAJAW6855G
	275 Gal	1040.87 L	MAJAW68TG
HYDRAULIC R&O	5 Gal	18.92 L	MAJR&O5G
	55 Gal	208.17 L	MAJR&O55G
	275 Gal	1040.87 L	MAJR&OTG



**Long
Lasting
MAXIMUM
PERFORMANCE**

Low Wear In Severe Industry
OEM Pump Specification Tests.



TYPICAL PROPERTIES

TYPE

Appearance
Viscosity cSt @ 40°C
Viscosity cSt @ 100°C
Pour Point, °C
Flash Point, °C
Viscosity Index

	32	46	68
Appearance	Amber, Bright, Free & Clear		
Viscosity cSt @ 40°C	32	46	68
Viscosity cSt @ 100°C	5.56	7.05	9.17
Pour Point, °C	-25	-27	-25
Flash Point, °C	215	220	220
Viscosity Index	110	110	110



PREMIUM GEAR OIL

Majestic gear oils are products that are developed and produced with performance additives to ensure protection against varnish and sludge, resulting in top-quality lubricants that meet or exceed the latest standards. The state-of-the-art technology in Majestic products delivers unsurpassed performance for low and high temperature applications, protection against thermal degradation and oxidation, service capability, and excellent fuel economy.



Product Availability

Majestic Advanced SAE 75W-90

5 Gal	18.92 L	MAI75W905G
55 Gal	208.17 L	MAI75W9055G
275 Gal	1040.87 L	MAI75W90TG

Majestic Advanced SAE 80W-140

5 Gal	18.92 L	MAJ80W1405G
55 Gal	208.17 L	MAJ80W14055G
275 Gal	1040.87 L	MAJ80W140TG

Majestic SAE 75W-90 and SAE 80W-140 Full Synthetic Gear Oils are formulated with synthetic base oils and premium gear additive packages to provide improved high-temperature thermal and oxidative stability in a wide range of operating conditions and advanced protection and lubricity in extreme pressure conditions. Majestic SAE 75W-90 and SAE 80W-140 Synthetic Gear Oils are highly shear stable while also resisting rust, oxidation, foaming, and varnish. These products are designed to exceed the year-around, all-weather performance viscosity requirements of SAE J306 as well as the rigorous performance requirements of API GL-5.

-Formulated with synthetic base oils and a premium gear additive package

-Formulated to provide improved high-temperature thermal and oxidative stability in a wide range of operating conditions

-Provide advanced protection and lubricity in extreme pressure conditions

-Highly shear stable while also resisting rust, oxidation, foaming, and varnish

-Designed to exceed the year-around, all-weather performance viscosity requirements of SAE J306 as well as the rigorous performance requirements of API GL-5

-Provides protection against the combination of thermal degradation, component wear, and oil seal deterioration



Product Availability

Majestic Advanced SAE 80W-90

5 Gal	18.92 L	MAJ80W905G
55 Gal	208.17 L	MAJ80W9055G
275 Gal	1040.87 L	MAJ80W90TG

Majestic Advanced SAE 85W-140

5 Gal	18.92 L	MAJ85W1405G
55 Gal	208.17 L	MAJ85W14055G
275 Gal	1040.87 L	MAJ85W140TG

Majestic SAE 80W-90 and SAE 85W-140 Conventional Gear Oils are formulated with high viscosity-index, paraffinic base oils and specialty performance additives to produce highly shear stable gear oils that resist rust, oxidation, foaming, and varnish. These products are designed for hypoids in automotive axles under high-speed and/or low-speed, high-torque conditions and provide advanced protection and lubricity in extreme pressure conditions.

-Formulated with high viscosity-index, paraffinic base oils and specialty performance additives

-Designed for hypoids in automotive axles under high-speed and/or low-speed, high-torque conditions

-Specialty anti-scuffing additives and friction modifiers

-Provides advanced protection and lubricity in extreme pressure conditions

-Highly shear stable

-Resists rust, oxidation, foaming, and varnish



Product Availability

Majestic Synthetic SAE-40

5 Gal	18.92 L	MAJSAE405G
55 Gal	208.17 L	MAJSAE4055G
275 Gal	1040.87 L	MAJSAE40TG

Majestic Synthetic SAE-50

5 Gal	18.92 L	MAJCD505G
55 Gal	208.17 L	MAJCD5055G
275 Gal	1040.87 L	MAJCD50TG

SAE 40 and SAE 50 (CD-50) Full Synthetic Heavy-Duty Manual Transmission Fluids are made with full synthetic (100% Synthetic) base stocks to extend drain intervals, improve fuel economy. This product is designed to have excellent cold-flow and anti-shear properties. SAE 40 and SAE 50 Full Synthetic Powershift Heavy-Duty Manual Transmission Fluids are formulated to provide superior protection against corrosion oxidation and wear.

-Extends drain intervals

-Improves fuel economy

-Superior protection corrosion and oxidation

-SAE 40 suitable for use in applications which require Eaton PS-188

-SAE 50 suitable for use in applications which require Rockwell/Eaton/Fuller CD-50 and Eaton PS-164 rev 7



Automatic Transmission Fluid

Majestic Full Synthetic Universal ATF (Allison TES-295) is formulated with 100% synthetic base stocks and premium performance additives to provide oxidation and thermal stability, friction control, load-carrying ability, as well as corrosion and wear protection. This product is designed for use in many makes and models of automatic transmissions including passenger cars, light trucks, heavy-duty trucks, commercial vehicles, as well as off-road vehicles.

Majestic Full Synthetic Universal ATF meets or exceeds TES-295 specifications and offers premium anti-shudder durability, friction stability, shift quality, anti-wear protection, oxidation stability, and outstanding low and high temperature operation characteristics.

Product Availability

1 Gal	3.78 L	MAJUATFG
5 Gal	18.92 L	MAJUATF5G
55 Gal	208.17 L	MAJUATF55G
275 Gal	1040.87 L	MAJUATFTG



Majestic SAE75W-80 Full Synthetic Transmission Fluid is a premium grade, full synthetic, heavy-duty transmission fluid formulated for optimal performance in Volvo iShift and Mack mDrive™ transmissions. This product contains a sophisticated additive system which provides synergistic benefits when combined with synthetic base oils in order to provide outstanding extended drain capabilities, extreme pressure protection, and exceptional oxidative and thermal stability. Further, this product is extremely shear stable and with optimized frictional characteristics for the recommended applications.

Product Availability

1 Gal	3.78 L	MAJ75W80G
5 Gal	18.92 L	MAJ75W805G
55 Gal	208.17 L	MAJ75W8055G
275 Gal	1040.87 L	MAJ75W80TG



Majestic Automatic Transmission Fluid (Dexron III / Mercon) is formulated with high viscosity-index paraffinic base stocks and premium performance additives for excellent oxidation stability, thermal resistance, and excellent friction modification properties. This product is suitable for power steering units where a Dexron III or Mercon fluid is recommended, and for mobile hydraulic and industrial systems, and rotary air compressors under specified service requirements.

Product Availability

5 Gal	18.92 L	MAJATF5G
55 Gal	208.17 L	MAJATF55G
275 Gal	1040.87 L	MAJATFTG



Formulated with high viscosity-index paraffinic base stocks and premium performance additives

Designed for excellent oxidation stability, thermal resistance, and excellent friction modification properties

Recommended where a Dexron-III/Mercon fluid is required

Suitable for power steering units where a Dexron III or Mercon fluid is recommended

Suitable for mobile hydraulic and industrial systems, and rotary air compressors under specified service requirements





PREMIUM

TRACTOR HYDRAULIC FLUID

Majestic Premium Tractor Hydraulic Fluid (John Deere J20C) is formulated with high-viscosity index base stocks and premium performance additives for use in transmissions, differentials, hydraulic, and power-steering units. Majestic Premium Tractor Hydraulic Fluid (J20C) is designed for all-season use in many different makes of tractors and farm equipment.



Product Availability

5 Gal	18.92 L	MAJHYD J20C5G
55 Gal	208.17 L	MAJHYD J20C55G
275 Gal	1040.87 L	MAJHYD J20CTG

- Formulated with high-viscosity index base stocks and premium performance additives
- Designed for use in transmissions, differentials, hydraulic, and power-steering units
- Designed for use in many different makes of tractors and farm equipment
- Designed for all-season use
- Specially blended to prevent rust, corrosion, foaming and oxidation
- Exceeds the performance of John Deere's J20C specification

SAE 30

DRIVETRAIN / TRANSMISSION FLUID

Majestic SAE 30 HD Transmission/ Drivetrain Oil (CAT TO-4) is a high-performance multi-purpose transmission and drivetrain fluid that is designed for powershift transmissions, final drives, wet brakes, differentials, hydraulic, and power-steering units. This product is formulated with high viscosity-index type II paraffinic base stocks and premium performance additives to provide maximum gear life and capacity for wet brakes and power-take-off clutches, excellent wet brake noise suppression and filterability characteristics. Majestic SAE 30 HD Transmission/ Drivetrain Oil (TO-4) is specially blended to prevent rust, corrosion, foaming and oxidation.



Product Availability

5 Gal	18.92 L	MAJDT305G
55 Gal	208.17 L	MAJDT3055G
275 Gal	1040.87 L	MAJDT30TG

- High-performance multi-purpose transmission and drivetrain fluid
- Designed for powershift transmissions, final drives, wet brakes, differentials, hydraulic, and power-steering units
- Formulated with high viscosity-index type II paraffinic base stocks and premium performance additives
- Provides maximum gear life and capacity for wet brakes and power-take-off clutches, excellent wet brake noise suppression and filterability characteristics
- Specially blended to prevent rust, corrosion, foaming and oxidation



HD1 Hi-TEMP MULTI-PURPOSE GREASE

Majestic Hi-Temperature NLGI No. 2 grease is a premium EP lithium complex grease that combines excellent multipurpose properties with a high dropping point and low-temperature pumpability that provides a wide operating temperature range. This product provides superior protection in heavily-loaded industrial applications.



- Wheel bearings in vehicles having drum brakes
- Smooth texture, non-melting, possess excellent shear stability
- Meets the highest performance categories of ASTM D-4950 Automotive Grease Classification System, GC for wheel bearing service and LB for chassis service

Product Availability

14 Oz	.40 kg	MAJHD1
35 Lb	15.88 kg	MAJHD135LB
120 Lb	54.43 kg	MAJHD1120LB
400 Lb	181.44 kg	MAJHD1400LB



CONVENTIONAL, HEAVY DUTY TRUCK & UNIVERSAL ANTIFREEZE/COOLANT



Majestic Red Antifreeze / Coolant is an ethylene glycol-based coolant for heavy-duty diesel, gasoline, and natural powered engines that protects your complete cooling system with no added SCA (Supplemental Coolant Additives) or testing required. Majestic Red Antifreeze is available as a concentrate and as 50/50 pre-diluted.

Majestic Green Antifreeze / Coolant is a premium, ethylene glycol antifreeze / coolant for use year-round in both aluminum and conventional metal engine cooling systems of automobiles, trucks, marine and stationary equipment and heavy-duty diesel engines (with the use of SCA). Formulated with a low silicate type rust and corrosion inhibitor system which effectively alleviates problems of gel formation and prevents loss of radiator heat transfer capacity. Majestic Green Antifreeze pre-diluted 50/50 is a 50/50 volume mixture of Antifreeze / Coolant with deionized water. For animal and child protection, Majestic Green Antifreeze / Coolant contains bitterant.

600,000 MILES / 965,606 KM / 12,000 HOUR SERVICE LIFE*

Available In Concentrate And Pre-Diluted 50/50 Formula

Receive up to 600,000 miles / 965,606 km or up to 12,000 hours with a complete flush and fill using Majestic Antifreeze coolant product.



Majestic Yellow Universal Antifreeze / Coolant is a nitrite-free, premium quality product that is compatible with all automotive and light duty truck antifreeze / coolant products in automobiles. Our antifreeze provides service life up to and exceeding 5 years or 241,402 kilometers. It is ideal for initial fills, coolant change-outs or top-offs. Majestic Yellow Universal Antifreeze / Coolant not only guards against freezing and boil-over, it also provides critical protection against corrosion forming on system components, including aluminum.



**Technologically
Advanced!**



Product Availability

Red Concentrate	6/ Gal	6/3.78 L	MAJRAF100G
	55 Gal	208.17 L	MAJRAF10055G
	330 Gal	1249.19 L	MAJRAF100TG
Red 50/50	6/ Gal	6/3.78 L	MAJRAFG
	55 Gal	208.17 L	MAJRAF55G
	330 Gal	1249.19 L	MAJRAFTG
Green Concentrate	6/ Gal	6/3.78 L	MAJGAF100G
	55 Gal	208.17 L	MAJGAF10055G
	330 Gal	1249.19 L	MAJGAF100TG
Green 50/50	6/ Gal	6/3.78 L	MAJGAFG
	55 Gal	208.17 L	MAJGAF55G
	330 Gal	1249.19 L	MAJGAFTG
Yellow Concentrate	55 Gal	208.17 L	MAJYAF10055G
	330 Gal	1249.19 L	MAJYAF100TG
Yellow 50/50	55 Gal	208.17 L	MAJYAF55G
	330 Gal	1249.19 L	MAJYAFTG



Our Majestic product line encompasses a full range of high-quality lubricants with applications across various industries. We manufacture and package synthetic and conventional products that include heavy duty engine oil, hydraulic oil, gear oil, transmission fluid, antifreeze, and grease, among others. We offer the full line of Majestic products in various sizes, including totes, drums, gallons, and quarts. Majestic products can also be purchased in bulk.

📍 Unit 19-20, 3615 Laird Rd,
Mississauga, ON

☎ 647-761-3033

✉ sales@majesticlubricantscanada.ca